

Power Crane

The **Power Crane** is designed to work on the 3-Point linkage of agricultural tractors of 60HP and up. Its main application is for lifting bags of fertiliser or meal, up to half a tonne in weight.



This product comes complete with brackets to attach a fertiliser spreader; with the spreader in place, large bags can easily be manoeuvered from a trailer over the spreader to dispense the load.

This system eliminates the need for a second tractor to load the spreader.

Key Features:

- Hydraulic lift & extension of the jib operated via valve chest, which is mounted on the side of the frame.
- Hose anti-burst valve for safe operation.
 In the unlikely event of a hose bursting while a ram is extended, it will be prevented from collapsing by the valve which shuts off the rapid expulsion of the oil.
- Valve chest for tractors with only one single acting service, so only a supply and return connection is required.
- GA1 Certified sling/hook included.

	Width	Max Height	Max Reach	Lift Capacity	Linkage	Net Weight	Tractor HP
Boom Retracted	1070mm <i>(42″)</i>	3786mm <i>(149″)</i>	1526mm <i>(60″)</i>	1000kg (2200lbs)	CAT 2	300kg (660lbs)	60+
Boom Extended	1070mm <i>(42″)</i>	4546mm <i>(179″)</i>	2357mm <i>(100″)</i>	500kg (1100lbs)			